



FiberLock™



- FORMERLY LABELED AS LOCKING FIBERS
- CRIMPED POLYESTER FIBERS EXACTLY 1/2 INCH IN LENGTH
- FIBERS INTERLOCK WITH EACH OTHER TO INCREASE THE MECHANICAL BOND OF ALL HYDRAULIC FIBER MULCH PRODUCTS
- INCREASES SLURRY SHOOTING DISTANCE

DIRECTIONS FOR USE

ADD FIBERLOCK TO YOUR HYDRAULIC SEEDER ONCE YOUR WATER LEVEL IS APPROXIMATELY 1/3 FULL. THEN LOAD SEED, FIBER MULCH AND FERTILIZER TO YOUR SLURRY AS YOU FINISH FILLING THE TANK. PLEASE REFER TO EQUIPMENT MANUFACTURER'S LOADING INSTRUCTIONS.

PHYSICAL PROPERTIES

POLYESTER	1/2 INCH CRIMPED
FIBER DIAMETER	4.5 DENIER
SURFACE TENSION	62.3 DYNES / CM
pH RANGE	6.71 +/- .2

APPLICATION RATE

< 4 TO 1 SLOPE	20 LBS PER ACRE
3 TO 1 SLOPE	20 LBS PER ACRE
> 2 TO 1 SLOPE	20 LBS PER ACRE

PACKAGING

10 LBS PER CASE, SHIPPED 72 CASES PER 48 x 48 Pallet



DISTRIBUTED BY